



VEXTRA

VEXTRA TADPOLE TAPE
01/03

STANDARD PUT UP: 100 FT LENGTHS

NOMINAL TAIL THICKNESS: 0.125"

NOMINAL WALL THICKNESS OF BULB: 0.060"

CONTENT: TAPE & ROPE MADE FROM 100% FIBERGLASS YARNS. COATED WITH VERMICULITE

TEMPERATURE RESISTANCE: FABRIC IS RATED AT 1000°F CONTINUOUS, REMAINS STABLE TO 1500°F WITH VERMICULITE COATING.

CONSTRUCTION: TAPE-WOVEN
BULB-KNITTED FIBERGLASS ROPE

NOMINAL OVERALL WIDTHS: 1", 1-1/8", 1-1/4", 1-3/8", 1-1/2", 1-3/4", 1-7/8", 2", 2-3/8", 2-1/2",
2-5/8", 2-3/4", 3"

NOMINAL BULB DIAMETERS: 3/8", 1/2", 5/8", 3/4", 1", 1-1/2"

TAPE FINISH: VERMICULITE IS AN INORGANIC, CHEMICALLY INERT, NONCOMBUSTIBLE &
ODORLESS COATING. NOTE: FIBERGLASS ROPE CORE INSIDE BULB IS NOT COATED.

OTHER: MATERIAL SHOULD BE TESTED FOR ITS SUITABILITY IN ANY APPLICATION, PARTICULARLY
FLEXING APPLICATIONS AT ELEVATED TEMPERATURES. USERS SHOULD ALSO FAMILIARIZE
THEMSELVES WITH THE MSDS BEFORE HANDLING.

ALL STATEMENTS HEREIN ARE EXPRESSIONS OF OPINION WHICH WE BELIEVE TO BE ACCURATE AND RELIABLE BUT ARE PRESENTED WITHOUT GUARANTEE OR RESPONSIBILITY ON OUR PART. ANYONE INTENDING TO USE RECOMMENDATIONS CONTAINED IN THIS PUBLICATION CONCERNING EQUIPMENT, PROCESSING TECHNIQUES OR PRODUCTS SHOULD FIRST SATISFY HIMSELF THAT THE RECOMMENDATIONS ARE SUITABLE FOR HIS USE AND MEET ALL APPROPRIATE SAFETY AND HEALTH STANDARDS.

Date of issue: 01/03

Date Revised:

Date Reviewed: 09/08

Revision No.: 0

DOCUMENT IS UNCONTROLLED IF PRINTED